

HEADQUARTERS

OFFICE: 15th floor,Rongchao Mansion,Longcheng Street,Longgang ,Shenzhen ,China

Tel: +86 755 8482 7256 E-mail: sales@zdtelecom.com www.ibscomponents.com www.zdtelecom.com Web:

Indoor Wide band Omni Antenna, coverage 380MHz - 2700MHz

	Specification	ıs			
Item No.		ZD380-2700H04i360A			
Frequency Range		MHz	380-520	698-960	1710-2700
Gain		dBi			4.5±1.0
Polarization			Horizontal		
VSWR			≤2.5	≤2.0	≤2.0
PIM, 3rd Order, 2 x 20 W,		dBc	/ ≤-140 ≤-140		
Input Power, maximum		watts	50		
Impedance		ohm	50		
Mechanica	l Specification	on			
Connector Type			N-female		
Size		mm	Ф266×18		
Antenna Weight		kg	0.4		
Mounting Kit			Ceiling, via hole (standard)		
Radome Material and Color			ABS, White, RAL9003		
Operational Temperature		оС	-55~60		
Operational Humidity		%	< 95		
Horizontal pattern	33	36 50 36 50	150	10 10 10 10 10 10 10 10 10 10 10 10 10 1	150
Vertical pattern	33	-10 00 -10 00 -30 00	100	38.00	38 39 39 39 39 39 39 39 39 39 39 39 39 39

Features and Product Description

- Wideband Omni Antenna, coverage 380MHz 2700MHz.
- Typically both used in indoor distribution of GSM/CDMA WIFI/3G/LTE 5G services.

800MHz

- Low return loss, Stable performance.
- Compact, light-weight and easy to install.
- Supplied with mounting clamp.
- PIM<-140dBc @ 2x20 W.



2500MHz

1710MHz